

Sr. No.	End Conn 1 Thread type NPT Male	End Conn 2 Thread type NPT Female	Model No. For MOC: SS316
1	1/8"	1/8"	SS-HA-2M-2F
2	1/8"	1/4"	SS-HA-2M-4F
3	1/8"	3/8"	SS-HA-2M-6F
4	1/8"	1/2"	SS-HA-2M-8F
5	1/4"	1/4"	SS-HA-4M-4F
6	1/4"	3/8"	SS-HA-4M-6F
7	1/4"	1/2"	SS-HA-4M-8F
8	3/8"	3/8"	SS-HA-6M-6F
9	3/8"	1/2"	SS-HA-6M-8F
10	1/2"	1/2"	SS-HA-8M-8F
11	1/2"	3/4"	SS-HA-8M-12F
12	1/2"	1"	SS-HA-8M-16F
13	3/4"	3/4"	SS-HA-12M-12F
14	3/4"	1"	SS-HA-12M-16F
15	1"	1"	SS-HA-16M-16F
16	1"	1.25"	SS-HA-16M-20F
17	1"	1.5"	SS-HA-16M-24F



Material Grade Selection Chart

For following Material Grade (MOC)	Replace First Two Letters of Model No. with following
SS316L	SSL
SS304	S4
SS304L	S4L
Brass	B
Alloy 400	ML
Alloy 600	INC
Alloy C276	HC
PTFE	T
Carbon Steel	CS

Note: Above Model Nos. are for NPT Threads, For BSP Threads Add -B & for BSPT Threads add -BT at end of Each Size in Model Nos.

Hex Adaptor shall be supplied with our standard short Length.

For Specific Length required for Hex Adaptor, add -Length in mm at the end of the Model No,

Head Office

"TRUEWAY HOUSE", Plot No. 535/14-15, Sonawala Cross Road No. 2, Nr. M.K. Industrial Estate, Goregaon (East), Mumbai - 400 063, INDIA. **Mobile : +91 9321756212, +91 9004146034 | Phone : +91 22 26852241, 26851052.**

E-mail

sales@truesdayindia.in

Website

www.truesdayindia.in